

Client: Holly Hunt
5025 W.73rd Street
Bedford Park
Illinois 60638
USA

Entry No: 65931

Date received: 07/07/2014

Client's Description: Sample of fabric: 503 / Imposter, Content: 58% Polyurethane - 42% Polyester

TEST REPORT

Test Required: Flammability BS 5852 : 1979 Ignition sources 0 & 1

Pre-treatment: None

Conditioning: A minimum of 96 hours at 50 +/- 20% Relative Humidity, 20 +/- 5°C

Method of Test: BS 5852 : Part 1 : 1979

Date of Test: 11/07/2014

The following test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

Ignition Source	Observations	Result
0 (cigarette)	No flaming or progressive smouldering was observed within one hour of placement of the cigarettes.	PASS
1 (butane flame)	Flaming ceased within the specified two minute period after removal of the butane flame and no progressive smouldering occurred.	PASS

Note: A 35 kg/m³ CM foam (Carpenters RX36-125) was used as the filling

-----End of Document-----

This is hereby certified to be a correct return of the tests made of the items referred to herein.




Geoff Briggs C.Text., A.T.I.
Head of laboratory
17th July 2014

- ❖ Unless instructed otherwise by the client sample remnants will be disposed of after 28 days
- ❖ Test marked (*) in this certificate are not included in the UKAS Accreditation Schedule for this Laboratory.
- ❖ Opinions and interpretations expressed herein are outside the scope of UKAS accreditation.
- ❖ This Certificate relates only to the sample received and, unless that sample has been drawn by the staff of this laboratory, or its agent, and endorsed accordingly, any application of the result to a bulk quantity or other material is entirely the responsibility of the client.

